
# Pallet Truck Scale

# **BTA425 / BTA445**





1500 or 2000 kg

Multi-interval:

BTA425 supplied with IND425

**BTA445** supplied with IND445

Multi-interval: 0-600 kg in 0.2 kg graduation

0.1 % of the applied load (non legal for trade)

Exchangeable battery module 12 Vdc / 1,2 Ah

switching off display at inclinations over 2 degrees)

Indication in display (charger 230 Vac / 12 Vdc included)

360 degrees with stop, for readout from different angles

600-1500 kg in 0.5 kg graduation

0-1000 kg in 0.5 kg graduation 1000-2000 kg in 1 kg graduation

Legal for trade conform EU-Specifications (incl. level switch for

2000 kg

Lifting capacity Weighing capacity Electronics

Graduations: Version 1500 kg

Version 2000 kg


Maximum error

Power supply Battery Autonomy Battery charging level

**Rotating indicator** 

Wheels

Color



## Rubber steering wheels Polyurethane loading wheels (tandem)

RAL 5003

8 hours

### DIMENSIONS

A = Fork length1B = Fork width1C = Fork height1D = Lifting height1E = Width over the forks1F = Top indicator height1

1150 mm 180 mm 85 mm (+/- 2 mm) 205 mm 555 mm (+/- 5 mm) 910 mm

### **OPTIONS**

Version legal for trade Integrated printer for printing out weights Extra exchangeable battery module Stainless steel fork shoes Different loading or steering wheels Different dimensions Footbrake





Νεύτων Τεχνολογίες ΑΒΕΕ Γέρακα 113.Τ.Θ. 67934 15344 Γέρακας Τηλ: 210 6654544 Fax: 210 6654545 marketing@nefton.gr www.nefton.gr

Rev.29.06.05.2