
# Stainless Steel version Pallet Truck Scale

## BTA429 / BTA449





## Specification sheet BTA429 and BTA449

Lifting capacity 2,000 kg

Weighing capacity 1,500 or 2,000 kg

**Electronics** BTA429 supplied with IND429

BTA449 supplied with IND449

**Graduation:** 

Version 1,500 kg Multirange: 0 - 600 kg : graduation 0.2 kg

600 - 1,500 kg : graduation 0.5 kg

Version 2,000 kg Multirange: 0 - 1,000 kg : graduation 0.5 kg

1,000 - 2,000 kg : graduation 1 kg

Maximum error 0.1 % of the applied load (non legal for trade)

Legal for trade conform EU-specifications (incl. level switch for

switching off display at inclinations over 2°)

**Power supply** Exchangeable battery module 12 Vdc/1.2 Ah


**Battery autonomy** 


**Battery charging level** Indication in display (charger 230 Vac/12 Vdc included)

**Rotating indicator** 360° with stop, for readout from different angles

Wheels Nylon steering wheels

Nylon loading wheels, single





### **DIMENSIONS** in mm

A = Fork length	1150
B = Fork width	170
C = Fork height	85
D = Lifting height	205
E = Width over the forks	550
F = Top indicator height	970
G = Pallet stop to indicator	55

#### **OPTIONS\***

Version legal for trade, OIML class III Integrated printer for printing out weights Extra exchangeable battery module Different loading or steering wheels Different dimensions

Footbrake

\*For special options the specifications can differ from standard specifications



TOLEDO METTLER