

The Affordable Solution for Quick, Accurate Weighing





Get More for Less with the PANTHER PLUS Scale Terminal

From its time and date feature to its ability to accommodate up to 10 targets, the PANTHER PLUS scale terminal gives you the power and performance required to satisfy all your weighing requirements.


PANTHER PLUS Terminal Specifications


| 1744111ER 1 EGG Tollimial Opodinoanono | | | | | | |
|--|---|--|--|--|--|--|
| Physical Dimensions (WxDxH) | 178 mm x 66 mm x 159 mm (7 in x 2.58 in x 6.25 in) | | | | | |
| Construction | Stainless steel construction to provide NEMA 4x and IP65 protection | | | | | |
| Power | Universal AC power supply works with 100, 120, 220, and 240 AC power sources | | | | | |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) | | | | | |
| Display | 7-digit, 7-segment vacuum fluorescent numeric display; 12.7 mm / 0.55 in high | | | | | |
| Keypad | 7- function, 11- key numeric | | | | | |
| Scale Performance | Internal resolution 1,000,000; External 10,000 | | | | | |
| Scale Interface | Maximum of eight 350 ohm analog load cells | | | | | |
| Scale Update Rate | >300 Hz | | | | | |
| Digital Filtering | METTLER TOLEDO's exclusive TraxDSP® filtering | | | | | |
| Process Control | 2 setpoints with preacts, zero tolerance | | | | | |
| Checkweighing | 10 targets with 5 zones each | | | | | |
| Time/Date | 24-hour clock, international format | | | | | |
| Discrete Outputs/Inputs | 3 outputs/1 input/5 zone status LEDs | | | | | |
| Shipping Weight | 2.5 kg (5.5 lb) | | | | | |
| Options | Analog Output - External I/O Box Weigh Modules, Bench Scales, Floor Scales, Load Cells | | | | | |


Standard Features:

- **Engineered from the Inside Out** Packaged in a stainless steel enclosure that meets NEMA 4X (IP65) requirements, it is ideal for use in just about any environment, including those requiring heavy washdown.
- Easy to Integrate The self-contained mounting bracket and line cord makes it easy to install. Just mount it on a desk or wall, hook up the load cell cable and built-in RS232 serial interface port, and you are ready to weigh.
- **Easy to Use** Setup, calibration, and a variety of weighing operations can be performed with only a few simple steps using the 11-button numeric keypad and function keys with universal symbols.
- Rapid Response Time Enhanced digital filtering, combined with the analog to digital weight conversions of more than 300 times a second, ensures that your weight data will be available when you need it.

*For more information, contact your authorized METTLER TOLEDO representative or one of the regional offices below.















Produced in a facility that is







| | | TEL | FAX | | TEL | FAX | |
|---|----------------|--------------------|--------------------|-----------------|-------------------|-------------------|---|
| USA 1900 Polaris Parkway Columbus, Ohio 43240 TEI (800) 523-5123 | Australia | (61-3) 9644 5700 | (61-3) 9645 3935 | Korea | (82-2) 518-2004 | (82-2) 518-0813 | Internet www.mt.com |
| | Austria | (43-1) 604 1980 | (43-1) 604 2880 | Malaysia | (60-3) 7845 5773 | (60-3) 7845 8773 | |
| | Belgium | (32-2) 334 0211 | (32-2) 378 1665 | Mexico | (52-5) 547 5700 | (52-5) 541 2228 | |
| | Brazil | (55-11) 4166-7400 | (55-11) 4166-7401 | Netherlands | (31-344) 638363 | (31-344) 638390 | Specifications subject to change without notice ©2002 Mettler-Toledo, Inc. |
| | Canada | (800) 638-8537 | (905) 681-8036 | Norway | (47) 22 30 44 90 | (47) 22 32 70 02 | |
| | China | (86-519) 6642040 | (86-519) 6641991 | Poland | (48-22) 651-9232 | (48-22) 651-7172 | |
| FAX (614) 438-4900 | Croatia | (385-1) 29 58 130 | (385-1) 29 58 140 | Russia | (7-095) 921 9211 | (7-095) 921 6353 | METTLER TOLEDO® and PANTHER® PLUS are registered trademarks of Mettler-Toledo, Inc. |
| | Czech Republic | (420-2) 721-23150 | (420-2) 721-23170 | Singapore | (65) 6890 0011 | (65) 6890 0012 | |
| Latin America Denmark TEL. (01) 305-351-2424 France FAX (01) 305-351-2425 Germany | Denmark | (45-43) 27 08 00 | (45-43) 27 08 28 | Slovak Republic | (421-2) 4342-7496 | (421-2) 4333-7190 | registered fidderfidiks of Mellier-Toledo, file. |
| | France | (33-1) 30 97 17 17 | (33-1) 30 97 16 16 | Slovenia | (386-1) 562-1801 | (386-1) 562-1789 | Printed in USA. |
| | Germany | (49-641) 50 70 | (49-641) 52951 | Spain | (34-93) 223-7600 | (34-93) 223-0271 | |
| Headquarters 8606 Greifensee | Hungary | (36-1) 288-4040 | (36-1) 288-4050 | Sweden | (46-8) 702 50 00 | (46-8) 642 45 62 | 3M0502 |
| | India | (91-22) 857-0808 | (91-22) 857-5071 | Switzerland | (41-1) 944 45 45 | (41-1) 944 45 10 | INSTRUMENTS |
| Switzerland | Italy | (39-02) 333321 | (39-02) 356-2973 | Taiwan | (886-2) 2579-5955 | (886-2) 2579-5977 | IN01015.2E |
| TEL. (41-1) 944 22 11 | Japan | (81-3) 5762-0706 | (81-3) 5762-0971 | Thailand | (66-2) 723-0300 | (66-2) 719-6479 | |
| FAX (41-1) 944 30 60 | Kazakhstan | (7-3272) 50 63 69 | (7-3272) 98 08 35 | United Kingdom | (44-116) 235 7070 | (44-116) 236 6399 | |